Car wheel change set with Click-Torque Lock: controlled tightening and loosening with only one tool

Now, wheel nuts & screws **can be loosened** with the Wera torque wrench **without damaging** the mechanics of the torque wrench.

How is that possible?

Well, by **deactivating** the torque function. Simple. Genius. Just slide the switch into the **Torque Lock position** and the torque function is deactivated and thus **protected**. Now, the torque wrench works as an extension with ratchet functionality.

No need for another loosening tool when changing wheels.
Your customers save time and money.

What else is unique about this torque tool?

An extra click. Audible and tactile fine adjustment of the torque value which ensures precise and secure setting.

- Robust Wera Impaktor design for extremely high stress
- Fast-rotating outer plastic sleeve to protect sensitive rim surfaces
- Internal plastic stop to protect the wheel nut/screw surfaces
- Beyond torque applications, also suitable for electric or pneumatic spanners
- Compact, clearly arranged and protected in a high-quality textile box
- With plastic mountings to lock and unlock the 3 Impaktor sockets

Click-Torque Lock C 3 car wheel change set 1

TORQUE TOOL | ADJUSTABLE | SWITCH | ON / OFF TORQUE LOCK | IMPACT PROOF | WHEEL SOCKET | FREE SPINNING SLEEVE

wera.de

- Measuring range: 40-200 Nm; precision ±3 % as per DIN EN ISO 6789-1:2017-07
- Torque Lock function: The torque function can be deactivated so that the tool can also be used for loosening
- Extra click: audible and tactile torque setting
- 3x 8790 C Wheel Impaktor sockets, ½", sizes 17.0; 19.0; 21.0
- The inner plastic insert of the sockets helps protect the surface of the wheel screws
- With Take it easy tool finder: colour coding by size
- The textile box can be fully unfolded; easy access to the tools inside

05**075790**001		
	Click-Torque Lock C 3	1x ½", 40-200 Nm
◉▣	**8790 C Wheel Impaktor**	1x 17,0x85,0x30,0; 1x 19,0x85,0x30,0; 1x 21,0x85,0x32,0
▣▢	**8894 SC**	1x ½"x125,0
	7762	1x 55,0x55,0x21,5

ON / OFF TORQUE LOCK

Click-Torque Lock: controlled tightening and loosening

With this torque wrench, not only controlled tightening of screws and bolts is possible. The brilliant Torque Lock function also allows for **loosening** screws and bolts.

Easy and safe

Easy setting and saving of the desired torque value; easy to read on main and fine scales.

Smooth plastic sleeve

The rotating plastic sleeve allows for higher control during screwdriving. In addition, the surface of the rim is protected. The plastic sleeves are interchangeable.

Wera Werkzeuge GmbH
Korzerter Straße 21–25
D-42349 Wuppertal
Germany
+49 (0)202 / 4045-0
info@wera.de
www.wera.de

Wera Tools (UK) LTD.
Railway View
Clay Cross
Chesterfield
Derbyshire
S45 9FR
+44 (0)1246 / 277756
queries@wera-tools.co.uk
weratools.co.uk

Wera Tools Inc.
(North America)
4129 Harvester Rd,
Unit H
Burlington, Ontario
Canada, L7L 5M3
1-800-267-55 41
info@weratools.com
www.weratools.com

Wera Tools Australia Pty Ltd.
Mike Sack
+61-435 755 123
mike.sack@wera.de
www.wera.de/en